



Manufactured for and Distributed  
Exclusively by Sherwin-Williams

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** DUCTILE IRON PIPE COATING HV  
**Other means of identification** None.  
**Recommended use** Not available.  
**Recommended restrictions** None known.  
**Manufacturer/Importer/Supplier/Distributor information**  
RR&C  
**Address** P.O. Box 67000  
Detroit, MI 48267-2791  
**Hours of Operation** 8:00 a.m. - 5:00 p.m.  
**Telephone Number** 1-216-515-7712  
**CHEMTREC** 1-800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Not classified.  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

### Label elements

**Hazard symbol** None.  
**Signal word** None.  
**Hazard statement** The mixture does not meet the criteria for classification.

### Precautionary statement

**Prevention** Observe good industrial hygiene practices.  
**Response** Wash hands after handling.  
**Storage** Store away from incompatible materials.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** None known.

**Supplemental information** Not applicable.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
WATER		7732-18-5	35 - 55
ASPHALT		8052-42-4	15 - 35
KAOLIN		1332-58-7	5 - 25
OXALIC ACID DEHYDRATE		6153-56-6	< 1

**Composition comments** Other components in this product are considered non-hazardous under the criteria specified in 29 CFR 1910.1200 (Hazard Communication Standard).

## 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.  
**Skin contact** If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.  
**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

<b>Ingestion</b>	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	Treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Water. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
<b>Fire fighting equipment/instructions</b>	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.
<b>Specific methods</b>	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	This product is miscible in water.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.
<b>Conditions for safe storage, including any incompatibilities</b>	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
KAOLIN (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

**US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
OXALIC ACID DEHYDRATE (CAS 6153-56-6)	PEL	1 mg/m <sup>3</sup>	

**US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)**

Components	Type	Value	Form
KAOLIN (CAS 1332-58-7)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m <sup>3</sup>	Inhalable fume.
KAOLIN (CAS 1332-58-7)	TWA	2 mg/m <sup>3</sup>	Respirable fraction.
OXALIC ACID DEHYDRATE (CAS 6153-56-6)	STEL	2 mg/m <sup>3</sup>	
	TWA	1 mg/m <sup>3</sup>	

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
OXALIC ACID DEHYDRATE (CAS 6153-56-6)	IDLH	500 mg/m <sup>3</sup>

**US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)**

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m <sup>3</sup>	Fume.
KAOLIN (CAS 1332-58-7)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total
OXALIC ACID DEHYDRATE (CAS 6153-56-6)	STEL	2 mg/m <sup>3</sup>	
	TWA	1 mg/m <sup>3</sup>	

**Biological limit values****ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
ASPHALT (CAS 8052-42-4)	2.5 µg/l	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Chemical goggles and face shield are recommended. Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

**Other**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact. Plastic or rubber gloves, apron and boots.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties**

<b>Appearance</b>	Heavy-consistency emulsion.
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Grey
<b>Odor</b>	Mild Petroleum Odor
<b>Odor threshold</b>	n/a
<b>pH</b>	> 5 - < 7
<b>Melting point/freezing point</b>	n/a
<b>Initial boiling point and boiling range</b>	>212 °F (>100 °C)
<b>Flash point</b>	>212.0 °F (>100.0 °C)
<b>Evaporation rate</b>	n/a
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	n/a
<b>Explosive limit - upper (%)</b>	n/a
<b>Vapor pressure</b>	60 mm Hg at 100°F, approx.
<b>Vapor density</b>	n/a
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Slightly
<b>Partition coefficient (n-octanol/water)</b>	n/a
<b>Auto-ignition temperature</b>	>400 °F (>204.44 °C)
<b>Decomposition temperature</b>	n/a
<b>Viscosity</b>	<7000 cP
<b>Viscosity temperature</b>	77 °F (25 °C)
<b>Other information</b>	
<b>Specific gravity</b>	> 1 - < 1.26
<b>VOC</b>	0.2 lb/gal maximum

**10. Stability and reactivity**

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable under normal temperature conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat product.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

**11. Toxicological information****Information on likely routes of exposure**

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	May be irritating to eyes.

**Ingestion** Expected to be a low ingestion hazard.  
**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

**Information on toxicological effects**

**Acute toxicity**

Components	Species	Test Results
ASPHALT (CAS 8052-42-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
KAOLIN (CAS 1332-58-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 5000 mg/kg
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** May be irritating to eyes.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not available.

**Skin sensitization** May cause skin disorders if contact is repeated or prolonged.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

ASPHALT (CAS 8052-42-4) Known To Be Human Carcinogen.

**Reproductive toxicity** Not available.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/chapping and oil acne.

**Further information** This product has no known adverse effect on human health.

**12. Ecological information**

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
DUCTILE IRON PIPE COATING HV		
<b>Aquatic</b>		
Crustacea	EC50 Daphnia	67787.4219 mg/l, 48 hours estimated

Product	Species	Test Results
<i>Acute</i>		
Crustacea	EC50	Daphnia
Fish	LC50	Fish
		8985.3486 mg/l, 48 hours estimated
		84.6021 mg/l, 96 hours estimated
Components	Species	Test Results
OXALIC ACID DEHYDRATE (CAS 6153-56-6)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna)
		>= 125 - <= 150 mg/l, 48 hours
<i>Acute</i>		
Crustacea	EC50	Water flea (Daphnia magna)
		125 - 150 mg/l, 48 hours

\* Estimates for product may be based on additional component data not shown.

<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	No data available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated material.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

### 14. Transport information

<b>DOT</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not available.

### 15. Regulatory information

<b>US federal regulations</b>	All components are on the U.S. EPA TSCA Inventory List.
<b>Toxic Substances Control Act (TSCA)</b>	
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	
	Not regulated.
<b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>	
ASPHALT (CAS 8052-42-4)	Listed.
<b>SARA 304 Emergency release notification</b>	
	Not regulated.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)</b>	
	Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

### SARA 311/312 Hazardous chemical

No

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ASPHALT (CAS 8052-42-4)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

### Safe Drinking Water Act (SDWA)

Not regulated.

## US state regulations

### California Proposition 65



**WARNING:** WARNING: This product contains a chemical known to the State of California to cause cancer.

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	08-06-2024
<b>Version #</b>	01
<b>Further information</b>	HMIS® is a registered trade and service mark of the NPCA.
<b>NFPA ratings</b>	Health: 1 Flammability: 1 Instability: 0

<b>References</b>	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
-------------------	--

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

**Revision information**

Product and Company Identification: Alternate Trade Names  
Hazard(s) identification: Response  
Hazard(s) identification: Hazard statement  
Fire-fighting measures: Suitable extinguishing media  
Fire-fighting measures: Unsuitable extinguishing media  
GHS: Classification